

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--|
| Deformaciones Verticales | 0,0000 | 0,0250 | 0,0500 | 0,0750 | 0,1000 | 0,1250 | 0,1500 | 0,1750 | 0,2000 | 0,2250 | 0,2500 | 0,2750 | 0,3000 | 0,3250 | 0,3500 | 0,3750 | 0,4000 | 0,4250 | 0,4500 | 0,4750 | 0,5000 | 0,5250 | 0,5500 | 0,5750 | 0,6000 | 0,6250 | 0,6500 | 0,6750 | 0,7000 | 0,7250 | 0,7500 | 0,7750 | |
| Deformaciones Unitarias (Dv/H) | 0,0000 | 0,0036 | 0,0071 | 0,0107 | 0,0143 | 0,0179 | 0,0214 | 0,0250 | 0,0286 | 0,0321 | 0,0357 | 0,0393 | 0,0429 | 0,0464 | 0,0500 | 0,0536 | 0,0571 | 0,0607 | 0,0643 | 0,0679 | 0,0714 | 0,0750 | 0,0786 | 0,0821 | 0,0857 | 0,0893 | 0,0929 | 0,0964 | 0,1000 | 0,1036 | 0,1071 | 0,1107 | |
| Area Corregida ((A/(Dv/H)) | 9,6200 | 9,6545 | 9,6892 | 9,7242 | 9,7594 | 9,7949 | 9,8307 | 9,8667 | 9,9029 | 9,9395 | 9,9763 | 10,0134 | 10,0507 | 10,0884 | 10,1263 | 10,1645 | 10,2030 | 10,2418 | 10,2809 | 10,3203 | 10,3600 | 10,4000 | 10,4403 | 10,4809 | 10,5219 | 10,5631 | 10,6047 | 10,6466 | 10,6889 | 10,7315 | 10,7744 | 10,8177 | |
| Lectura deform. del aro de carga (ingreso de datos) | 0,0000 | 4,0000 | 6,8000 | 12,0000 | 15,0000 | 20,2000 | 29,5000 | 29,2000 | 33,2000 | 36,2000 | 39,2000 | 41,8000 | 44,2000 | 45,0000 | 45,9000 | 46,5000 | 47,5000 | 48,2000 | 49,0000 | 50,0000 | 51,0000 | 51,8000 | 52,0000 | 52,0000 | 52,0000 | 50,0000 | | | | | | | |
| Carga aplicada (Lect. x factor aro) | 0,0000 | 2,1040 | 3,5768 | 6,3120 | 7,8900 | 10,6252 | 15,5170 | 15,3592 | 17,4632 | 19,0412 | 20,6192 | 21,9868 | 23,2492 | 23,6700 | 24,1434 | 24,4590 | 24,9850 | 25,3532 | 25,7740 | 26,3000 | 26,8260 | 27,2468 | 27,3520 | 27,3520 | 27,3520 | 26,3000 | 0,0000 | 0,0000 | 0,0000 | 0,0000 | 0,0000 | 0,0000 | |
| Presión axial | 0,0000 | 0,2179 | 0,3692 | 0,6491 | 0,8084 | 1,0848 | 1,5784 | 1,5567 | 1,7634 | 1,9157 | 2,0668 | 2,1957 | 2,3132 | 2,3463 | 2,3842 | 2,4063 | 2,4488 | 2,4755 | 2,5070 | 2,5484 | 2,5894 | 2,6199 | 2,6198 | 2,6097 | 2,5995 | 2,4898 | 0,0000 | 0,0000 | 0,0000 | 0,0000 | 0,0000 | 0,0000 | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Lectura deform. del aro de carga (ingreso de datos) | 0,0000 | 5,0000 | 8,0000 | 15,0000 | 18,0000 | 25,0000 | 31,3000 | 33,2000 | 36,5000 | 39,4000 | 42,5000 | 44,6000 | 46,1000 | 48,3000 | 50,5000 | 52,7000 | 54,6000 | 56,1000 | 57,9000 | 58,3000 | 60,1000 | 62,2000 | 63,5000 | 65,7000 | 68,0000 | 72,1000 | 73,8000 | 75,2000 | 76,6000 | 77,1000 | 77,1000 | | |
| Carga aplicada (Lect. x factor aro) | 0,0000 | 2,6300 | 4,2080 | 7,8900 | 9,4680 | 13,1500 | 16,4638 | 17,4632 | 19,1990 | 20,7244 | 22,3550 | 23,4596 | 24,2486 | 25,4058 | 26,5630 | 27,7202 | 28,7196 | 29,5086 | 30,4554 | 30,6658 | 31,6126 | 32,7172 | 33,4010 | 34,5582 | 35,7680 | 37,9246 | 38,8188 | 39,5552 | 40,2916 | 40,5546 | 40,5546 | 0,0000 | |
| Presión axial | 0,0000 | 0,2724 | 0,4343 | 0,8114 | 0,9701 | 1,3425 | 1,6747 | 1,7699 | 1,9387 | 2,0851 | 2,2408 | 2,3428 | 2,4126 | 2,5183 | 2,6232 | 2,7272 | 2,8148 | 2,8812 | 2,9623 | 2,9714 | 3,0514 | 3,1459 | 3,1992 | 3,2972 | 3,3994 | 3,5903 | 3,6605 | 3,7153 | 3,7695 | 3,7790 | 3,7640 | 0,0000 | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Lectura deform. del aro de carga (ingreso de datos) | 0,0000 | 5,0000 | 7,8000 | 13,0000 | 16,0000 | 21,2000 | 31,0000 | 32,2000 | 35,2000 | 38,3000 | 41,5000 | 43,8000 | 46,0000 | 47,0000 | 50,0000 | 51,0000 | 53,0000 | 55,0000 | 57,0000 | 60,0000 | 63,0000 | 66,0000 | 69,0000 | 72,0000 | 75,0000 | 78,0000 | 81,0000 | 83,0000 | 86,0000 | 89,0000 | 91,2 | 93,1 | |
| Carga aplicada (Lect. x factor aro) | 0,0000 | 2,6300 | 4,1028 | 6,8380 | 8,4160 | 11,1512 | 16,3060 | 16,9372 | 18,5152 | 20,1458 | 21,8290 | 23,0388 | 24,1960 | 24,7220 | 26,3000 | 26,8260 | 27,8780 | 28,9300 | 29,9820 | 31,5600 | 33,1380 | 34,7160 | 36,2940 | 37,8720 | 39,4500 | 41,0280 | 42,6060 | 43,6580 | 45,2360 | 46,8140 | 47,9712 | 48,9706 | |
| Presión axial | 0 | 0,27241 | 0,42344 | 0,70319 | 0,86235 | 1,13847 | 1,65869 | 1,71661 | 1,86967 | 2,02685 | 2,18809 | 2,3008 | 2,40738 | 2,45054 | 2,59719 | 2,63918 | 2,73233 | 2,82469 | 2,91628 | 3,05805 | 3,19865 | 3,33808 | 3,47633 | 3,61342 | 3,74933 | 3,88407 | 4,01764 | 4,10064 | 4,23206 | 4,36231 | 4,45233 | 4,52691 | |

| | | | | | | | | | | | | | | | | | | | | | | |
|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| 0.0000 | 0.8250 | 0.8500 | 0.8750 | 0.9000 | 0.9250 | 0.9500 | 0.9750 | 1.0000 | 1.0250 | 1.0500 | 1.0750 | 1.1000 | 1.1250 | 1.1500 | 1.1750 | 1.2000 | 1.2250 | 1.2500 | 1.2750 | 1.3000 | 1.3250 | 1.3500 |
| 0.8443 | 0.1179 | 0.1214 | 0.1250 | 0.1286 | 0.1321 | 0.1357 | 0.1393 | 0.1429 | 0.1464 | 0.1500 | 0.1536 | 0.1571 | 0.1607 | 0.1643 | 0.1679 | 0.1714 | 0.1750 | 0.1786 | 0.1821 | 0.1857 | 0.1893 | 0.1929 |
| 10.8613 | 10.9053 | 10.9496 | 10.9943 | 11.0393 | 11.0848 | 11.1306 | 11.1768 | 11.2233 | 11.2703 | 11.3176 | 11.3654 | 11.4136 | 11.4621 | 11.5111 | 11.5605 | 11.6103 | 11.6606 | 11.7113 | 11.7624 | 11.8140 | 11.8661 | 11.9186 |

[illegible][illegible][illegible]